

*** READ & SAVE THESE INSTRUCTIONS ***
MODEL: 23091 (FIXTURE ONLY)
INSTALLATION & OPERATION INSTRUCTIONS

(1) TOOLS AND MATERIALS REQUIRED

- ❖ BLADE & PHILIPS SCREW DRIVER
- ❖ ADJUSTABLE WRENCH
- ❖ STEP LADDER
- ❖ WIRE CUTTERS
- ❖ WIRING SUPPLIES AS REQUIRED BY ELECTRICAL CODE
- ❖ 1X18W/GU24

Attention:

Before assembling your lighting fixture, please read the following instructions. If you feel you do not have sufficient electrical experience, refer to a do-it-yourself wiring handbook or have your fixture installed by a qualified licensed electrician.

(2) GENERAL

1. To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning
2. All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified licensed electrician
3. These fixtures are intended for mounting to a standard 4" x 2 1/4" deep metal octagon junction box. The box must be directly supported by the building structure and U.L. recognized.
4. Before commencing with the installation, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box. Turning the power off using the light switch is not sufficient to prevent electrical shock.

NOTE:

The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care are factors that cannot be built into any product. These factors must be supplied by the person(s) caring for and operating the fixture.

(3) UNPACKING THE FIXTURE

On checking the contents of the box you will find;

- ❖ Fixture Assembly
- ❖ Mounting Hardware Package
- ❖ U-shaped bracket

(4) PREPARING THE FIXTURE

Refer to figure for illustration of fixture parts and assembly.

1. If you are replacing an existing fixture, disconnect and remove the old fixture. Expose the supply wiring from the **(1)J-box**.
2. Lay the un-assembled fixture on a soft surface and carefully remove all the packing material.
3. Feed fixture wires through the **(11)Spider ring** and the **(9)Canopy** orderly as per figure.
4. Determine the desired length for your fixture cable, trim and cut the cable to the desired length. Feed the cable through the **(8) Cord strain relief** as per figure, then pull it tightly.
5. Mount the **(4)U-shaped bracket** to the **(1)J-box** with the supplied **(5)Mounting screws**.
6. Connect the black supply wire to the black wire of the fixture, the white supply wire to the white wire of the fixture, the ground wires from the fixture to the ground wire of the J-box with the supplied **(2) Wire connectors**, secure wire connectors with U.L. listed electrical tape (not included).
7. Position the **(9)Canopy** over the **(4)U-shaped bracket** such that the holes on the sides of the **(9)Canopy** line up with the holes in the **(4)U-shaped bracket**. Secure the **(9)Canopy** to the **(4)U-shaped bracket** with the supplied **(7)Screws**.
8. Insert bulb into socket. **DO NOT EXCEED WATTAGE AS PER CAUTION LABEL.**
9. Release the **(12)Rods** from the **(11)Spider ring**, place the **(12)Rods** through the round holes on the **(13)Shade** to secure the **(13)Shade** against the **(11)Spider ring**.
10. Restore electricity and enjoy your new fixture.

CAUTION:

- Ensure that the Fitting is Cool and Switched off, Before Changing the Bulb.
- Do Not use Bulbs Exceeding Maximum Wattage, As Per Caution Label.
- Do Not Operate the Lighting Fixture close to any Combustible Material.

PLEASE SEE DIAGRAM ON REVERSE SIDE OF PAGE

access

LIGHTING

FIGURE

