

# access

L I G H T I N G

## Read & Save these Instructions Model: 52045 Installation & Operation Instructions

### (1) TOOLS AND MATERIALS REQUIRED

- ❖ BLADE & PHILIPS SCREW DRIVER
- ❖ ADJUSTABLE WRENCH
- ❖ STEP LADDER
- ❖ WIRE CUTTERS
- ❖ WIRING SUPPLIES AS REQUIRED BY ELECTRICAL CODE
- ❖ 1 X A-19/100W Lamp (medium base)

#### Attention:

Before assembling your lighting fixture, please read the following instructions. If you feel you do not have sufficient electrical experience, refer to a do-it-yourself wiring handbook or have your fixture installed by a qualified licensed electrician.

### (2) GENERAL

1. To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning
2. All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified licensed electrician
3. These fixtures are intended for mounting to a standard 4" \* 2 1/4" deep metal octagon junction box. The box must be directly supported by the building structure and U.L. recognized.
4. Before commencing with the installation, **disconnect the power by turning off the circuit breaker or** by removing the fuse at the fuse box. Turning the power off using the light switch is not sufficient to prevent electrical shock.

#### NOTE:

The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care are factors that cannot be built into any product. These factors must be supplied by the person(s) caring for and operating the fixture.

### (3) UNPACKING THE FIXTURE

On checking the contents of the box you will find;

- ❖ Fixture Assembly
- ❖ Glass Shade
- ❖ Mounting Hardware Package
- ❖ U-shaped bracket
- ❖ Optional Rods

### (4) PREPARING THE FIXTURE

*Refer to figure for illustration of fixture parts and assembly.*

1. If you are replacing an existing fixture, disconnect and remove the old fixture. Expose the supply wiring from the **(1)J-box**.
2. Lay the un-assembled fixture on a soft surface and carefully remove all the packing material.
3. Take off the **(13) Fitter ring** from the **(11) Fixture**, and take care of all parts to avoid missing.
4. Prepare the fixture by placing **(8)Rod-3** through the hole in the **(7)Canopy**.
5. Feed both the fixture and ground wire up through the rods (Rods-1, 2 and 3) to the **(7)Canopy**.
6. Screw **(10) Rod-1** onto the nipple protruding from the **(11)Fixture**. Screw the remaining rods together (Rod-2 to Rod-1 and Rod-3 to Rod-2).
7. Mount the **(4)U-shaped bracket** to the **(1)J-box** with the supplied **(5)Mounting screws**.
8. Wind the **(3) Fixture ground wire** on the **(14)Green screw** in **(4) U-shaped bracket**. Connect the **(3) Fixture ground wire** to the ground wire of the J-box, the black supply wire to the black wire of the fixture, the white supply wire to the wire of the fixture with the supplied **(2) Wire connectors**, secure wire connectors with U.L. listed electrical tape (not included).
9. Position the **(7)Canopy** over the **(4)U-shaped bracket** such that the holes on the sides of the **(7)Canopy** line up with the holes in the **(4)U-shaped bracket**. Secure the **(7)Canopy** to the **(4)U-shaped bracket** with the supplied **(6)Screws**.
10. Place the **(12) Glass shade** into the **(11) Fixture** and secure with the **(13) Fitter ring**. Take care when assembling or disassembling the **(12) Glass shade** to avoid breakage of the **(12) Glass shade**.
11. Insert bulb into socket. **DO NOT EXCEED WATTAGE AS PER CAUTION LABEL.**
12. Restore electricity and enjoy your new fixture.

#### CAUTION:

- *Ensure that the Fitting is Cool and Switched off, Before Changing the Bulb.*
- *Do Not use Bulbs Exceeding Maximum Wattage, As Per Caution Label.*
- *Do Not Operate the Lighting Fixture close to any Combustible Material.*

**PLEASE SEE DIAGRAM ON REVERSE SIDE OF PAGE**