

access

LIGHTING

INSTALLATION INSTRUCTIONS

IMPORTANT

Before assembling your access lighting fixture, please make sure that you carefully read through these instruction sheets. Consider having your fixture installed by a qualified licensed electrician.

NOTE: The important safeguards and instructions that appear in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care, are factors that can't be built into any product. These factors must be supplied by the person(s) caring for and operating the fixture.

GENERAL INFORMATION

All electrical connections must be in accordance with all ordinances, Local and National Electrical Codes. These fixtures are intended for mounting to a standard 4" x 2 1/2" metal octagon outlet box. The box must be directly supported by the building structure and U.L. Recognized.

STEP BY STEP INSTRUCTIONS

Before starting your installation disconnect the Power by turning off the Circuit Breaker or by removing the fuse at the fuse box. Just turning the light off at the light switch is not sufficient to prevent electrical shock.



COLLECTION
Sail

APPLICATION
Wall Fixture


MODEL NO.
70025LED

WHAT WE PROVIDE

- Back Plate
- Mounting Hardware
- 1 x Crossbar
- 1 x Metal Cover
- 14W LED

WHAT YOU NEED


- Screwdriver
- Wire Cutters
- Wiring Supplies as Specified by Electrical Code



1

MOUNT CROSSBAR PLATE


If there is an existing fixture remove it.
Mount the crossbar with bracket to the J-box with the supplied screws.



2

MAKE WIRE CONNECTIONS


Gently pull the supply wires through the hole in the crossbar . Gently feed the fixture wire through one of the slits in the back plate and then through the hole floating canopy. Connect the black supply wire to the black fixture wire. Secure with the supplied wire nuts. Connect the white supply wires to the white fixture wire. Secure with the supplied wire nuts. Either wrap the green wire around one of the protruding screws or connect it to the supply ground wire. Secure all wire with electrical tape (not supplied). Tuck all wires carefully into the J-Box.



3

MOUNT FIXTURE TO THE CROSSBAR PLATE


Position the fixture plate over the crossbar plate. Align the holes at the left and right of the plates. Secure with the supplied screws.



4

CONNECT LED CONNECTOR

Position the black supply wire to the black fixture wire and the red supply wire to the red fixture wire. Connect the LED Connector.



5

HOLD THE METAL COVER.

Holding the Metal cover into the Frame.



6

**RESTORE THE ELECTRICITY AND
CHECK THE OPERATION OF YOUR
NEW ACCESS FIXTURE**

CAUTION

Please ensure that the fitting is cool and switched off before replacing the bulb. DO NOT use bulbs that might exceed the maximum wattage, stated on caution label.