

THREE STATION FLOOR MOUNTED SINK WITH TUBULAR LEGS & CROSS BRACING

WITH/WITHOUT MANUAL FAUCETS



8 1/2" high backsplash.

8" sink bowl depth.

Two stainless steel "Z" brackets.

One K-6 3 1/2" rear basket drain.

Tubular stainless steel legs with flanged feet.

Side & rear adjustable cross-bracing with leg clamps.

Manual Operated: Faucets sold separately.

"-F" Series includes three K-159 3 1/2" gooseneck faucets.

CONSTRUCTION:

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish.



"-F" Series Sink Includes K-159 Gooseneck Faucets

Item #: _____ Qty #: _____ Model #: _____ Project #: _____





MATERIAL:

All 16 gauge type "304" stainless steel.

1 5/8" tubular "304" stainless steel legs & cross-bracing. Stainless steel gussets.

MECHANICAL:

8" O.C. faucet holes punched at each station.

		# of Faucets Sink	# of Faucets		Cu.
Model #	Length	Accommodates	Included	Wt.	Ft.
FC-FM-60	60"	3	0	94 lbs.	22
			(Faucets Not Included)		
FC-FM-60-F	60"	3	3	100 lbs.	22
			(K-159 Faucets Included)		



MULTI-STATION ACCESSORIES & REPLACEMENT PARTS Model **Description** QTY: 3 1/2" Drain (1 1/2" I.P.S.) **™** K-6 **F** K-13 Stainless Steel Soap Dispenser (Wall Mount Only) **™** K-06 Splash Mount Faucet Mounting Kit **K-101** 8" Swing Spout Splash Mt. Faucet K-101 K-159 **K-159** Splash Mounted 3-1/2" Gooseneck Faucet (8" O.C.) Splash Mounted 6" Swivel Spout Faucet (8" O.C.) **K-160** K-160 Strainer Plate for 3-1/2" Drain **K-411** Extra H.D. 8" Splash Mounted Faucet **K-1118** K-316-LU Wrist Handles K-472 Faucet Hole Revision (Manual Faucet Operated Sinks Only) K-508 Special Sizing Charge (Larger Size Cut Down To Smaller Size) K-06 K-13 **TA-19** Adjustable Stainless Steel Flanged Bullet Foot

Ships UPS

Standard Faucets conform to NSF 61 Standard 9 and compliance to AB 1953 Standards.

MARNING: Equipment that include faucets on this page may contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 7:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933

TOL ± .500" FITTINGS SUPPLIED AS SHOWN ALL DIMENSIONS ARE TYPICAL



