

FOUR STATION A.D.A. FLOOR MOUNTED SINK WITH TUBULAR LEGS & CROSS BRACING

WITH/WITHOUT MANUAL FAUCETS



8 1/2" high backsplash.

5" sink bowl depth.

Two stainless steel "Z" brackets.

One K-6 3 1/2" rear basket drain.

Tubular stainless steel legs with flanged feet.

Rear and side adjustable cross-bracing with leg clamps.

Manual Operated: Faucets sold separately.

"-F" Series includes four K-161-LU 3 1/2" gooseneck faucets with wrist handles.

CONSTRUCTION:

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish.



"-F" Series Sink Includes K-161-LU Gooseneck Faucets with Wrist Handles

Item #:	Qty #:
Project #:	







MATERIAL:

All 14 gauge type "304" stainless steel.

1 5/8" tubular "304" stainless steel legs & cross-bracing. Stainless steel gussets.

MECHANICAL:

8" O.C. faucet holes punched at each station.

		# of Faucets Sink	# of Faucets		Cu.
Model #	Length	Accommodates	Included	Wt.	Ft.
FS-FM-80-ADA	80"	4	0	130 lbs.	28
			(Faucets Not Included)		
FS-FM-80-ADA-F	80"	4	4	138 lbs.	28
			(K-161-LU Faucets Included)		

Click Here For Install Guide

MULTI-STATION ACCESSORIES & REPLACEMENT PARTS Model Description QTY: 3 1/2" Drain (1 1/2" I.P.S.) **™** K-6 **K-13** Stainless Steel Soap Dispenser (Wall Mount Only) Splash Mount Faucet Mounting Kit **■** K-06 **K-101** 8" Swing Spout Splash Mt. Faucet **K-159** K-159 Splash Mounted 3-1/2" Gooseneck Faucet (8" O.C.) **K-160** Splash Mounted 6" Swivel Spout Faucet (8" O.C.) K-160 **K-411** Strainer Plate for 3-1/2" Drain Extra H.D. 8" Splash Mounted Faucet **K-1118** K-316-LU Wrist Handles K-472 Faucet Hole Revision (Manual Faucet Operated Sinks Only) K-508 Special Sizing Charge (Larger Size Cut Down To Smaller Size) K-13 **TA-19** Adjustable Stainless Steel Flanged Bullet Foot

= Ships UPS

Standard Faucets conform to NSF 61 Standard 9 and compliance to AB 1953 Standards.

📤 WARNING: Equipment that include faucets on this page may contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 7:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933

TOL ± .500" FITTINGS SUPPLIED AS SHOWN ALL DIMENSIONS ARE TYPICAL



