





Hand Sinks With Glass Rinser





Model #	Size L x W x H	Approx. Weight	Approx. Cu. Ft.
PRCS-25-12	12" x 25" x 36"	65 lbs.	7
PRCS-25-18	18" x 25" x 36"	80 lbs.	9

REPLACEMENT PARTS



K-125 6" Splash Mounted Faucet



SU-16 Glass Rinser



A-33 Dipper Well Faucet (For PRCS-25-18)



A-10 1" Water Outlet For Drainboard



A-7 Dipper Well (For PRCS-25-18)



K-63 1-1/2" Drain

Item #: _____ Qty #: ___ Model #: _____ Project #: _

FEATURES:

K-125 splash mount swing spout faucet 29" working height

7" backsplash

Stainless steel top, apron, sides, legs and adjustable bullet feet

Stainless steel glass rinser with removable drainboard Adjustable stainless steel side cross-bracing

Additional Features:

PRCS-25-12 - One Piece Deep Drawn 9" x 9" x 4" sink bowl with 2" drain with strainer plate

PRCS-25-18 - One Piece Deep Drawn 14" x 10" x 7" sink bowl with 2" drain with strainer plate Dipper well with A-33 faucet

MATERIAL:

Sink: 20 gauge, 300 stainless steel Glass Rinser: 18 gauge stainless steel

K-125 Sink Faucet: Splash mounted, chrome plated

brass body, chrome plated handle

Legs: 1-5/8" O.D. 18 gauge, 300 stainless steel with

1" adjustable stainless steel bullet feet

PRCS-25-18 Only:

Dipper Well: Stainless steel insert

A-33 Dipper Well Faucet: Deck mounted, chrome

plated brass body, chrome plated handle

MECHANICAL:

Sink: 1-1/2" IPS outlet drain

Glass Rinser: 4-1/2" Glass Rinser Area Water Connection: External - 1/2" BSP (Standard Plumbing Connection)

Sink Drain: Threaded Brass 1-1/2" x 1/2" ID, 1" IPS Dipper Well (PRCS-25-18 Only): 1-1/2" IPS drain

Water Connection for Dipper Well & Glass Rinser: External - 1/2" BSP (Standard Plumbing Connection)

OPTIONAL



A-16 Perforated Basket A-17A Perforated Basket (Fits PRCS-25-18)



(Fits PRCS-25-12)



**WARNING: Faucets on this page may expose you to chemicals, including lead, that are known to the State of California to cause cancer or birth defects or other reproductive harm. For more Info., visit www.p65warnings.ca.gov.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 7:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Ouotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933

DIMENSIONS and SPECIFICATIONS

TOL Overall: ± .500" Interior: ± .250"

ALL DIMENSIONS ARE TYPICAL



