





50 CFM/0.7 Sones @ 0.10" SP. 39 CFM @ 0.25" SP.

• Grill

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 10³/₄" x 11³/₄".

Blower Wheel

One piece polymeric wheel 51/8" diameter, 23/8" wide, with 48 fins.

Motor

Heavy duty, permanently split capacitor, plug-in, 4 pole motor, life time lubrication, thermally protected, suitable for continuous operation. Rated 120 volts, 60 hz.

Fan Housing

PC/ABS polymeric, dimensions 81/2" x 91/8" x 37/8".

Oval Duct Collar


Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation. Oval design accepts standard 4" round ducting and fits into standard 2" x 4" walls.


Ventilating Area

For bathrooms up to 45 sq. ft. For other rooms up to 60 sq. ft.

Single Pack Shipping Info

Box Dim: $11^{1}/_{16}$ " x 14" x $6^{3}/_{16}$ " UPC: 0-8316294156-5 Shipping Weight: $5^{1}/_{4}$ lbs.





Oval duct collar allows fan to be installed into walls using standard 2" x 4" studs.

Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.





Unit Mounting

Designed to mount in walls or ceilings with at least 4" of clearance. The unit is mounted directly to the joist or stud using a separate lock-in bracket (included with unit). The housing will mount through drywall thickness up to 3/4", with a rough-in opening of 8/2" x 9/8".

Suitable for wall insert mounting when discharged vertically and mounted outside of shower enclosure

EXPANDED PERFORMANCE												
									Sones	Fan Speed	Maximum	
	Static Pressure (inches of w.g.)							@ .1 SP	RPM	Fan Watts	Amps	
	0	0.1	0.125	0.15	0.2	0.25	0.3	0.35				
Air Flow - CFM	52	50	49	48	47	39	37	35	0.7	1064	13.5	0.3

PROJECT								ARCHITECT			
LOCATION							ENGINEER				
CONTRACTOR							SUBMITTED BY DATE				
FAN Number	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS		





U.S.: 820 Lincoln Avenue
West Chester, Pennsylvania 19380-4466
Tel: (610) 692-7400 ● 877-304-3785
Fax: (610) 696-8048

Brampton, Ontario Tel: 905-456-2033 Fax: (905) 456-1015

Canada:

Specifications subject to change without notice. Updated 7-21