





80 CFM/2.0 Sones @ 0.10" SP.

• <u>Grill</u>

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - $10^{3}/4^{"} \times 11^{3}/4^{"}$.

• Blower Wheel

One piece polymeric wheel $5^{1/8}$ " diameter, $2^{3/8}$ " wide, with 48 fins.

• Motor

Heavy duty, permanently split capacitor, plug-in, 4 pole motor, life time lubrication, thermally protected, suitable for continuous operation. Rated 120 volts, 60 hz.

• Fan Housing

PC/ABS polymeric, dimensions 81/2" x 91/8" x 43/4".

• Duct Collar


Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

• Ventilating Area

For bathrooms up to 65 sq. ft. For other rooms up to 85 sq. ft.

• Single Pack Shipping Info

Box Dim: 11¹/₁₆" x 12" x 6⁵/₁₆" UPC: 0-8316290302-0 Shipping Weight: 5¹/₄ lbs.



Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.



• Unit Mounting

Designed to mount in ceilings with at least 6" of clearance. The unit is mounted directly to the joist using a separate lock-in bracket (included with unit). The housing will mount through drywall thickness up to 3/4", with a rough-in opening of 811/16" x 91/8".

				EXF	PANDE	D PER	FORM/	ANCE				
	Static Pressure (inches of w.g.)							Sones @ .1 SP	Fan Speed RPM	Maximum Fan Watts	Amps	
	0	0.05	0.1	0.125	0.15	0.2	0.25					
Air Flow - CFM	87	84	80	78	75	69	66	2.0	1347	29.0	0.3	
PROJECT						ARCHITE	CT					
LOCATION						ENGINEE	R					
CONTRACTOR						SUBMITTED BY D/			DATE			
FAN MODEL NUMBER NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS				
				U.S.: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 • 877-304-3785							ı, Ontario 156-2033	
							. ,	696-8048		Fax: (905	Fax: (905) 456-1015	