

SPECIFICATIONS DS SERIES RANGE HOODS

180 CFM/6.5 SONES @ 0.10" SP. Horizontal 180 CFM/6.5 SONES @ 0.10" SP. Vertical

Dimensions

Overall bottom projection - 183/8" Overall top projection -12" Height - 6"

Available widths: 30" & 36"

Hood Body

Stainless Steel: 24 gauge, grade 430 stainless steel.

Painted: 23 gauge cold rolled commercial grade (CRCQ) steel, auto welded, coated with a baked enamel finish.

Motor

Variable speed, single coil, thermally protected, permanently lubricated. Rated 120 volts, 60 hz. Complete with 200°C lead wires.

<u>Lighting</u>

Single 60 watt cook light capacity (bulb not included) complete with night light setting.

Ducting Options


Horizontal ducting: 31/4"x10" (duct adapter and damper included). Vertical ducting: 31/4"x10" (duct adapter and damper included). Vertical ducting: 7" round (duct adapter and damper not included). Ductless: removable front vent (charcoal filter not included).

Fan Blade


One piece polymeric, electronically balanced blade. $65/8\ensuremath{^{"}}$ diameter with 5 paddles.

Electrical connection

Hood top - 7/8" electrical knockout. Hood back - 7/8" electrical knockout.



DS SERIES



Filters

UL rated, class 2 filter. Grease Filter: RF35 - 87/8"x103/8" (included). Charcoal Filter: RF34 (not included). Combo Grease/Charcoal: RF55 (not included).

Available Finishes

White, Biscuit, Almond, Black & Stainless Steel.

EXPANDED PERFORMANCE											
		Stati	c Pressure	e (inches d	Sones	Fan Speed	Power				
Air Flow - CFM	0	0.05	0.1	0.15	0.2	0.25	@ .1 SP	RPM	Watts	Apms	
Vertical Ducting	210	200	180	160	140	125	6.5	2800	85.0	1.5	
Horizontal Ducting	210	200	180	160	140	125	6.5	2800	85.0	1.5	

PROJECT							ARCHITECT			
LOCATION							ENGINEER			
CONTRACTOR							SUBMITTED BY DATE			
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	





Air King: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 • 877-304-3785 Fax: (610) 696-8048

Brampton, Ontario Tel: 905-456-2033 Fax: (905) 456-1015

Canada:

Specifications subject to change without notice.

Updated 4-20