





250 CFM/6.0 Sones (Horizontal) @ 0.10" SP. 100 CFM/1.5 Sones (Horizontal) @ 0.03" SP. 220 CFM/6.5 Sones (Vertical) @ 0.10" S.P. 120 CFM/1.5 Sones (Vertical) @ 0.03" S.P.

## • Dimensions

Overall bottom projection - 18%" Overall top projection -12" Height - 6" Available widths: 30" & 36"

## Hood Body

Stainless Steel: 24 gauge, grade 430 stainless steel. Painted: 23 gauge cold rolled commercial grade (CRCQ) steel, auto welded, coated with a baked enamel finish.

## Motor

Fully enclosed PSC 4 pole motor. 2 speed, thermally protected, permanently lubricated. Rated 115/120 Volts, 60 hz.

## • Lighting


Includes 6 Watt GU24 base LED lamp (included). 4 watt night light (bulb not included)


## • Ducting Options

Horizontal ducting: 3<sup>1</sup>/<sub>4</sub>"x10" (duct adapter and damper included). Vertical ducting: 3<sup>1</sup>/<sub>4</sub>"x10" (duct adapter and damper included). Vertical ducting: 7" round (duct adapter and damper not included). Ductless: removable front vent (charcoal filter not included).

## Blade

Polymeric axial fan blade 9<sup>1</sup>/<sub>8</sub>" diameter with 7 paddles.





# • Electrical connection

Hood top -  $\frac{1}{8}$ " knockout hole for use with  $\frac{1}{2}$ " cable clamp Hood back -  $\frac{1}{8}$ " knockout hole for use with  $\frac{1}{2}$ " cable clamp

## Filters

UL rated, class 2 filter. Grease Filter: GF-08 (included). Charcoal Filter: CF-08 (not included).

Available Finishes
 White, Black & Stainless Steel.



Updated 11-20

		:	XPAN	DED F	PERFO	RMANC	E			
	Static Pressure (inches of w.g.)						Sones	Fan Speed	Maximum	
Air Flow - CFM	0	0.03	0.1	0.125	0.15	0.2	@ .1 SP	RPM	Fan Watts	Amps
Horz Ducting High Speed	300	280	250	230	220	188	6.0	1673	72.0	
Horz Ducting Working Speed	131	100	-	-	-	-	1.5	917	18.0	
Vert Ducting High Speed	280	256	220	199	195	163	6.5	1682	72.0	0.6
Vert Ducting Working Speed	158	130	-	-	-	-	1.5	970	18.0	
FAN MODEL CFM V	IN RPM WATTS AMPS				SONES	TTED BY DATE DATE OPTIONAL EQUIPM COPTIONAL EQUIPM COPTIO				
US CREPT	Air King: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 • 877-304-3785							<b>Canada:</b> Bramptor Tel: 905-4		
Intertek ENERGY STAR	THE OF ARB	A				Fax: (610) 696-8048 Fax: (905) 456-101				

\* The ENERGY STAR Program for Residential Ventilating Fans has no provision for qualification of ductless range hoods (recirculating not ventilating), as a result the ENERGY STAR program applies to ducted range hoods only. Specifications subject to change without notice.