AKDO°

EXCALIBUR ARMOR SHINING Metal



PART NUMBER PROFILE AVAILABILITY
AL2259-ARMR00 MOSAIC IN STOCK

VARIATION GROUT JOINT DIMENSIONS

LOW BUTT JOINTED 11.88" \times 12" = .99 sqft (+/-)

THICKNESS

3mm

NOTES

Metal mosaics do not need to be sealed, however check with your grout manufacturer to see if your grout should be sealed.

When using metals in a backsplash design, include a 4" splash guard of wet area appropriate material in areas where water may pool, such as behind faucets.

APPLICATION AREA

WALL	FLOOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET 2 AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	No	No	No	Yes	No	YES - Heat not to exceed 392° F	YES - Heat not to exceed 392° F

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.