

## ORIGIN 10 1/2" X 1/2" LINER CORNER MUSHROOM (M) Ceramic

PART NUMBER PROFILE AVAILABILITY

CR2501-LNCRMO TRIM IN STOCK

VARIATION GROUT JOINT THICKNESS

LOW 1/16" 3/8"

NOTES

Due to the inherent characteristics of ceramic, there may be variations in color, movement and texture from lot to lot.

## APPLICATION AREA

WALL FLOOR EXTERIOR STEAM WET POOL BACKSPLASH FIREPLACE SURROUND

Yes No No No Yes Yes No Yes Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

## TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Bond Strength - EN 14411	> 1 N/mm2	Breaking Strength - ISO 10545-4	Compliant
Coefficient of Thermal Linear Expansion - ISO 10545-8	< 7*10-61/4C-1	Crazing Resistance - ISO 10545-11	Resistant
Bending Resistance - ISO 10545-4	Compliant	Reaction to Fire - EN 14411	Al
Regularity of Length & Width - ISO 10545-2	Compliant	Regularity of Rectangularity - ISO 10545-2	Compliant
Regularity of Straightness of Sides - ISO 10545-2	Compliant	Resistance to Household Chemicals - ISO 10545-13	GA
Resistance to Swimming Pool Salts - ISO 10545-13	GA	Surface Flatness - ISO 10545-2	Compliant
Water Absorption - ISO 10545-3	Compliant		