


## ARCHITETTO ANGOLO CALACATTA (H) W/ BRASS Stone, Man





PART NUMBER PROFILE AVAILABILITY
MB1203-ANGOH1 MOSAIC IN STOCK

VARIATION GROUT JOINT DIMENSIONS HIGH 1/16" 8" x 8" = .444 sqft

THICKNESS 3/8"

NOTES

As a natural material, brass is prone to oxidation; a chemical reaction that occurs over time from exposure to air.

## APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET	POOL	BACKSPLASH
Yes	Brass may scratch when used as floor covering	Light Commercial	No	No	No	No	YES - Heat not to exceed 293° F

FIREPLACE SURROUND

YES - Heat not to exceed 293° F

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

Epoxy grout should be used when installing Architetto mosaics with metal.

## TECHNICAL DATA

FEATURES & STANDARD SPECIFICATION FEATURES & STANDARD SPECIFICATION

DCOF - ANSI A. 137.1