


12" X 24" THASSOS PREMIUM (P) *Stone, Marble*



PART NUMBER	PROFILE	AVAILABILITY
MB1232-1224PO	TILE	IN STOCK
VARIATION	GROUT JOINT	DIMENSIONS
LOW	1/8"	12" x 24" = 2 sqft (+/-)
THICKNESS		
3/8"		

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot. It is important to properly seal marble used in a shower/steam shower, and maintain the sealant regularly to ensure water beads off the tile.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Standard Commercial	No	YES - when properly sealed	YES - when properly sealed	No	Yes
FIREPLACE SURROUND							
Yes							

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
DCOF - ANSI A.137.1			