

PERSPECTIVE AXIS THASSOS (P) W/CARRARA (H) Stone, Marble



PART NUMBER PROFILE AVAILABILITY

MB1232-AXISPO MOSAIC IN STOCK

VARIATION GROUT JOINT DIMENSIONS

 $11.16'' \times 13.5'' = 1.05 \text{ sqft}$

THICKNESS 3/8"

MEDIUM

NOTES

 $\label{eq:decomposition} Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.$

1/16"

It is important to properly seal marble used in a shower/steam shower, and maintain the sealant regularly to ensure water beads off the tile.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Standard Commercial	No	YES - when properly sealed	YES - when properly sealed	No	Yes

FIREPLACE SURROUND

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installation from more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
DCOF - ANSI A 137 1			