

ETHEREAL STELLA CARRARA BELLA (H) W/ STAINLESS STEEL Stone, Marble, Metal



PART NUMBER PROFILE AVAILABILITY

MB1604-STLAHO MOSAIC IN STOCK

GROUT JOINT DIMENSIONS THICKNESS

1/16" 10.25" \times 8.75" = .63 sqft 3/8" with 0.4cm Stainless Steel I

NOTES

Epoxy grout should be used when installing ethereal mosaics. for more information, please download the ethereal collection's installation guidelines.

APPLICATION AREA

WALL FLOOR TRAFFIC EXTERIOR STEAM WET POOL BACKSPLASH
FREEZE/THAW SHOWER AREA

Yes Yes Standard No No YES - when properly No YES - Heat not to exceed 293° F

FIREPLACE SURROUND

YES - Heat not to exceed 293° F

DCOF - ANSI A. 137.1

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA FEATURES & STANDARD SPECIFICATION FEATURES & STANDARD SPECIFICATION SPECIFICATION

akdo.com