


NOMAD 24" X 24" TURCHESE (M) *Porcelain*



PART NUMBER
PO1968-242400

VARIATION
MEDIUM

THICKNESS
3/8"

NOTES
Available nationwide.

PROFILE
TILE

GROUT JOINT
1/16"

AVAILABILITY
IN STOCK

DIMENSIONS
23.64" x 23.64" = 3.87 sqft

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Light Commercial	Yes	Yes	Yes	Yes	Yes	Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-7	Class 4=PEI 2100 G1R1	Chemical Resistance - ASTM C650	Resistant
Chemical Resistance - ISO 10545-13	Resistant	DCOF - ANSI A.137.1	> 0.42
Frost Resistance - ASTM C1026	Resistant	Frost Resistance - ISO 10545-12	Resistant
Bending Resistance - ASTM C648	> 35N/mm ₂	Bending Resistance - ISO 10545-4	> 35N/mm ₂
Resistance to Household Chemicals - ISO 10545-13	GA	Resistance to Swimming Pool Salts - ISO 10545-13	GA
Thermal Shock Resistance - ASTM C484	Resistant	Water Absorption - ASTM C373	≤ 0.5%
Water Absorption - ISO 10545-3	≤ 0.5%		