

## RENAISSANCE 24" X 24" CHARMING (P) *Porcelain*



PART NUMBER  
PO2315-2424PO

PROFILE  
TILE

AVAILABILITY  
IN STOCK

GROUT JOINT  
1/16"

DIMENSIONS  
23.64" x 23.64" = 3.875 sqft

THICKNESS  
3/8"

### NOTES

Available nationwide.  
Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

### APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM	WET	POOL
Yes	Residential Use Only	Floor Residential	Yes FREEZE/THAW	Wall Only SHOWER	Wall Only AREA	Yes
BACKSPLASH	FIREPLACE					
Yes	Yes SURROUND					

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

### TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-6	Compliant	Breaking Strength - ISO 10545-4	Compliant
Coefficient of Thermal Linear Expansion - ISO 10545-8	± 7 10-6°C-1	DCOF - ANSI A.137.1	> 0.42 Wet
Frost Resistance - ISO 10545-12	Compliant	Coefficient of Restitution - ISO-10545-5	Compliant
Bending Resistance - ISO 10545-4	Compliant	Moisture Expansion - ISO 10545-10	± 0.01% (0.1mm/m)
Reaction to Fire - EN 13501-1	A1fl	Regularity of Length & Width - ISO 10545-2	Compliant
Regularity of Rectangularity - ISO 10545-2	Compliant	Regularity of Straightness of Sides - ISO 10545-2	Compliant
Resistance to Household Chemicals - ISO 10545-13	A	Resistance to Swimming Pool Salts - ISO 10545-13	A
Booted Ramp Test - DIN 51130	R10	Surface Flatness - ISO 10545-2	Compliant
Water Absorption - ISO 10545-3	0.2%		

### LEED

MR	MR	MR	MR
Recycled Content	Regional Materials	Sustainability Report	Environmental Product Declaration
13,8%	32%	Available self-declared Corporate Sustainability Report (CSR) conform to Global Reporting Initiative (GRI) Sustainability Report	Available industry-wide Environmental Product Declaration (EPD) conform to ISO14025

MR	EQ	SS	EA	ID
Material Ingredients	Low Emitting Materials	Heat Island Effect	Energy Performance	Innovation & Design

Available Health Product Declaration (HPD) in compliance with the Health Product Declaration Open Standard

No VOCs Emission

Light Color SRI > 26

COMMERCIAL 1.3 W/m<sup>2</sup>K

HOSPITALITY

RESIDENTIAL