## **AKDO**°

## TRADITION 47" X 110" ALPINE WHITE (M) SLAB Porcelain



PART NUMBER PROFILE REPEAT PO2421-SL14M0 SLAB 20

AVAILABILITY DIMENSIONS **THICKNESS** IN STOCK 47.24" x 110.24" = 36.16 sqft

.6cm

NOTES

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

## APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET R AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Heavy Commercial	Yes	Yes	Yes	Yes	Yes	Yes

Available nationwide.

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

## TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-7	Class 4	Breaking Strength - ISO 10545-4	<sup>3</sup> 1350 N
DCOF - ANSI A.137.1	> 0.42 wet	Frost Resistance - ISO 10545-12	Resistant
Bending Resistance - ISO 10545-4	> 52 N/mm2	Regularity of Length & Width - ISO 10545-2	±0.15%
Regularity of Rectangularity - ISO 10545-2	±0.2%	Regularity of Straightness of Sides - ISO 10545-2	±0.1%
Surface Quality - ISO 10545-2	Conforming	Resistance to Household Chemicals - ISO 10545-13	GA
Resistance to Swimming Pool Salts - ISO 10545-13	GA	Surface Flatness - ISO 10545-2	±0.2%
Water Absorption - ISO 10545-3	0.08% (average)		