

MASON 12" X 24" IVORY (SOFT) *Porcelain*



PART NUMBER
PO2465-1224ST

PROFILE
TILE

REPEAT
40

AVAILABILITY
IN STOCK

GROUT JOINT
1/16"

DIMENSIONS
11.81" x 23.62" = 1.937 sqft

THICKNESS
10mm

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Heavy Commercial	Yes	Yes	Yes	Yes	Yes	Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-6	140	Barefoot Ramp Test - DIN 51097	A
Breaking Strength - ISO 10545-4	3200 N	DCOF - ANSI A.137.1	> 0.42 Wet
Frost Resistance - ISO 10545-12	Resistant	Bending Resistance - ISO 10545-4	50 N/mm2
Regularity of Length & Width - ISO 10545-2	± 0.15%	Regularity of Rectangularity - ISO 10545-2	± 0.2%
Regularity of Straightness of Sides - ISO 10545-2	± 0.1%	Surface Quality - ISO 10545-2	Compliant
Resistance to Household Chemicals - ISO 10545-13	UA	Resistance to Swimming Pool Salts - ISO 10545-13	UA
Booted Ramp Test - DIN 51130	R9	Surface Flatness - ISO 10545-2	± 0.35%
Water Absorption - ISO 10545-3	0.08%		

LEED

MR	MR	MR	MR
Recycled Content	Regional Materials	Sustainability Report	Environmental Product Declaration
7,1%	38%	Available self-declared Corporate Sustainability Report (CSR) conform to Global Reporting Initiative (GRI) Sustainability Report	Available industry-wide Environmental Product Declaration (EPD) conform to ISO 14025

MR	EQ	SS	EA	ID
Material Ingredients	Low Emitting Materials	Heat Island Effect	Energy Performance	Innovation & Design
Available Health Product Declaration (HPD) in compliance with the Health Product Declaration Open Standard	No VOCs Emission	Light Color SRI > 29	1,0 - 1,3 W/mK	Certificate Greenguard