

## CONCRETE JUNGLE 2" X 2" FACTORY (SOFT) *Porcelain*



APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Standard Commercial	Yes	Yes	Yes	Yes	Yes	Yes

PART NUMBER  
**PO2523-M002ST**

PROFILE  
**MOSAIC**

AVAILABILITY  
**IN STOCK**

DIMENSIONS  
**11.81" x 11.81" = .970 sqft**

THICKNESS  
**10mm**

### TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-6	145 mm <sup>3</sup>	Breaking Strength - ISO 10545-4	Thick. 10mm: 2.500 N
Chemical Resistance - ISO 10545-13	LA, HA Resistant	Coefficient of Thermal Linear Expansion - ISO 10545-8	$\alpha = 7.6 \times 10^{-6} \text{ } ^\circ\text{C}^{-1}$
Shade Variation - ANSI A 137.1	V3	DCOF - ANSI A.137.1	>0.42
Frost Resistance - ISO 10545-12	Resistant	Bending Resistance - ISO 10545-4	50 N/mm <sup>2</sup>
Fire Reaction - EN 9239-1	Class A1fl (floor)	Fire Reaction - EN 13823	Class A1 (wall)
Regularity of Length & Width - ISO 10545-2	Compliant	Regularity of Rectangularity - ISO 10545-2	Compliant
Regularity of Straightness of Sides - ISO 10545-2	Compliant	Slip Resistance - ANSI A326.3	DCOF <sup>3</sup> 0.42
Water Absorption - ISO 10545-3	0.05%	Thermal Conductivity - EN 12524	$\lambda = 1.3 \text{ W/m } ^\circ\text{K}$

### LEED

MR	MR	EQ	ID
Recycled Content	Environmental Product Declaration	Low Emitting Materials	Innovation & Design
40% Pre-Consumer Recycled Material	Available industry-wide Environmental Product Declaration (EPD)	No VOCs Emission	Certificate GOLD Greenguard