

SIO SOLID BEIGE HEX (M) *Porcelain*



PART NUMBER
PO2541-HEXAM0

VARIATION
LOW

THICKNESS
3/8"

NOTES

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

PROFILE
TILE

GROUT JOINT
1/16"

AVAILABILITY
IN STOCK

DIMENSIONS
7.87" x 9.06" = .377 sqft

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Residential Medium Commercial	Yes	Yes	Yes	Yes	Yes	Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Chemical Resistance - ISO 10545-13	GLA	Crazing Resistance - ISO 10545-11	Resistant
DCOF - ANSI A.137.1	> 0.42	Frost Resistance - ISO 10545-12	Resistant
Resistance to Household Chemicals - ISO 10545-13	GA	Resistance to Swimming Pool Salts - ISO 10545-13	GA
Water Absorption - ISO 10545-3	Eb ² 0.5%	Pei Rating	Group 4

LEED

EQ	MR	MR
Low Emitting Materials	Material Ingredient Reporting	Material Ingredient Optimization
No VOCs emission	Red List Free	Compliant with the Restrictions of Reach and are free of the SVHC listed on the candidate list.