

PLAZA NUEVA MIRAMAR GRAY (M) Porcelain



PART NUMBER PROFILE AVAILABILITY
PO2573-HEXA00 TILE IN STOCK

VARIATION GROUT JOINT DIMENSIONS LOW 1/16" $7.87" \times 9.06" = .377 \text{ sqft}$

THICKNESS 3/8"

NOTES

 $\label{eq:decomposition} \mbox{Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.}$

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET R AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Residential and	Yes	Yes	Yes	Yes	Yes	Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Chemical Resistance - ISO 10545-13	GLA	Crazing Resistance - ISO 10545-11	Resistant
DCOF - ANSI A.137.1	> 0.42	Frost Resistance - ISO 10545-12	Resistant
Resistance to Household Chemicals - ISO 10545-13	GA	Resistance to Swimming Pool Salts - ISO 10545-13	GA
Water Absorption - ISO 10545-3	Eb ² 0.5%	Pei Rating	Group 3

LEED

EQ MR MR

Low Emitting Materials Material Ingredient ReportingMaterial Ingredient Optimization

No VOCs emission Red List Free Compliant with the Restrictions of Reach and are free of the SVHC

listed on the candidate list.