

F907-110

Opera Flexible Hose Hand Shower Kit on Pivoting Hook

artos®

OPERATING SPECIFICATIONS



OPERATING TEMPERATURE

Maximum: 176°

Minimum: 50°

OPERATING PRESSURE

Minimum: 15psi

Maximum: 75psi

Recommended: 20psi-70psi

Above 90psi it may be necessary to install a pressure reducer.

MATERIAL

Solid Brass

ABS

REQUIREMENTS

Control Valve

FLOW RATE

1.8 USGPM

FEATURES

Easy Clean Jet Nozzles

Integrated Backflow Preventer (CV-15)

150cm wand reach

STANDARDS

To view all standards, please visit product approvals in our learning hub at artos.us.com

All technical specifications, product details, and pricing are subject to change without prior notice. Artos makes every effort to ensure accuracy; however, errors or omissions may occur. It is the responsibility of the installer, designer, or purchaser to verify all critical dimensions, installation requirements, and compliance with applicable codes prior to use.

Artos assumes no liability for damages, losses, or injuries resulting from the use of this documentation or from product installation, operation, or maintenance performed outside of Artos instructions and applicable codes. Product warranties are limited to those expressly stated by Artos. Please refer to official warranty documentation for complete terms and conditions.

All drawings, manuals, and specifications are the property of Artos and may not be reproduced, distributed, or altered without prior written permission.

F907-110

Opera Flexible Hose Hand Shower Kit on Pivoting Hook

PRODUCT SKU: F907-110

artos®

PRODUCT DIMENSIONS

