

# F908-8

Harmony Wall Mounted Tub Filler

artos®

## OPERATING SPECIFICATIONS



### OPERATING TEMPERATURE

Maximum: 176°

### OPERATING PRESSURE

Minimum: 10psi

Maximum: 125psi

Recommended: 15psi-75psi

Above 90psi, it may be necessary to install a pressure reducer

### FLOW RATE

6.1 USGPM

### INLET/OUTLET CONNECTIONS

3/4" Female NPT

### MATERIAL

Solid Brass

### REQUIREMENTS

This unit requires a control

### FEATURES

Articulating Aerator

### STANDARDS

To view all standards, please visit product approvals in our learning hub at [artos.us.com](https://artos.us.com)

All technical specifications, product details, and pricing are subject to change without prior notice. Artos makes every effort to ensure accuracy; however, errors or omissions may occur. It is the responsibility of the installer, designer, or purchaser to verify all critical dimensions, installation requirements, and compliance with applicable codes prior to use.

Artos assumes no liability for damages, losses, or injuries resulting from the use of this documentation or from product installation, operation, or maintenance performed outside of Artos instructions and applicable codes. Product warranties are limited to those expressly stated by Artos. Please refer to official warranty documentation for complete terms and conditions.

All drawings, manuals, and specifications are the property of Artos and may not be reproduced, distributed, or altered without prior written permission.

# F908-8

Harmony Wall Mounted Tub Filler

artos®

## PRODUCT DIMENSIONS

PRODUCT SKU: F908-8

