

**Pintbrook® 0.125 GPF
High Efficiency Urinal System**

- ❑ **6002.525** 0.125 gpf Exposed Top Spud Urinal and Selectronic® Urinal Flush Valve

URINAL:

- Vitreous china
- High Efficiency operates in the range of 0.125 gpf to 0.50 gpf (0.47 Lpf/1.9 Lpf)
- Powerful washdown action
- Optimized chinaware contours provide superior splash protection
- 3/4" inlet top spud
- Outlet connection threaded 2" NPT
- Wall hangers included
- Made in Mexico (NAFTA compliant)
- Model 6002.001.020

SELECTRONIC® FLUSH VALVE:

- Factory-Installed CR-P2 Lithium Battery
- Pressure compensation feature ensures accurate flush volume regardless of inlet water pressure
- Self-Cleaning Piston
- Integral wiper spring cleans refill orifice with every flush, preventing clogging and run-on
- No routine maintenance required. No diaphragm to change; no filter screen to clean.
- Dezincification resistant semi-red brass alloy
- Fully mechanical manual override button can flush the valve without power
- Valve remains closed and does not need to be reset after loss of water pressure
- Adjustable sanitary flush cleans the fixture and maintains the trap seal.
- Stadium feature: valve automatically switches to water savings mode during periods of heavy usage
- High back pressure vacuum breaker prevents leaking
- Chloramine-resistant EPDM seals
- Adjustable tailpiece for rough-in flexibility
- Can be installed left or right handed
- No external volume adjustment
- ADA compliant
- Model 6063.013.002

Includes:

- 2 Wall hangers
- 3/4" I.P.S. angle stop with back-flow protection and vandal-resistant cap
- Sweat solder kit including cover tube and wall flange
- 3/4" High back pressure vacuum breaker, spud coupling and flange



SEE REVERSE FOR ROUGHING-IN DIMENSIONS

High-Efficiency Urinal Systems:

- 87.5% water savings when compared to a 1.0 gpf urinal system

Battery Life:

- 4 years @ 4,000 flushes per month

Operating Pressure:

20 psi (flowing)-80 psi (static)

Flow Requirement:

10 gpm (37.9 L/min.)

Nominal Fixture Dimensions:

366 x 364 x 575 mm
(14-7/16" x 14-5/16" x 22-5/8")



5-YEAR LIMITED
WARRANTY on
FIXTURE and
FLUSH VALVE



EPA
WATERSENSE
CERTIFIED

