

Clinic Service Sink Floor Mount

9504.999.020

- Vitreous china
- Floor mount
- Flushing rim
- Siphon jet flushing action
- 1-1/2" top spud
- White Only
- Includes bolt caps

FLUSH VOLUME: 6.5 gpf / 24.6 Lpf

OPERATING PRESSURE: 25 psi (flowing) - 80 psi (static)

FLOW REQUIREMENT: 25 gpm (96.6 L/min.)

Available Components:

- 710098-201.081** Pedestal base, black on white finish
- 7832504.075** Rim guard, service sink, floor

Nominal Dimensions:

743 x 508 x 457mm
(29-1/4" x 20" x 18")

NOTES:

- Fixture conforms to ANSI/ASME A112.19.2M standards
- Optional one, two or three rim guards available when specified and ordered accordingly (not shown)
- Optional pedestal base (approximately 28"x14"x10") available when specified and ordered accordingly (as shown)
- Flush valve specifications: Flush valve with 1" angle stop, 1-1/2" vacuum breaker and flush connection.

FLUSH VALVE RECOMMENDATION:

American Standard 6047117.002 or equivalent

OPTIONAL ACCESSORIES

- Bedpan Diverter: American Standard 6047800.002 / 6047815.002 or equivalent
- Service Sink Faucet: American Standard 8345.115 or equivalent

NOTES:

- * CUSTOMER SHOULD CHECK WITH GENERAL CONTRACTOR TO DETERMINE IF BASE IS BEING PROVIDED BEFORE PROCEEDING WITH ROUGHING-IN MEASUREMENTS.
- ** VARIABLE-CHECK WITH MANUFACTURER OF FLUSHVALVE FOR PROPER ROUGHING-IN DIMENSIONS.
- *** VARIABLE-CHECK WITH MANUFACTURER OF SERVICE SINK FAUCET FOR PROPER ROUGHING-IN DIMENSIONS.

IMPORTANT: Roughing-in dimensions may vary 1/2" and are subject to change or cancellation without prior notice. No responsibility is assumed for use of superseded or voided leaflets.

Available in White Only

