


Water-Saving Pressure Balance Bath/Shower Trim

with Double Ceramic Pressure Balance Cartridge



MODEL NUMBER:

TRIM KITS:

☐ TU106508 Patience Bath/Shower Trim Kit with **Pressure Balance Cartridge**

Lever handle. Water-saving showerhead. LESS valve body.

☐ TU106507 Patience Shower ONLY Trim Kit with Pressure Balance Cartridge

FINISHED WALL

Lever handle. Water-saving showerhead. LESS valve body.

For use with Flash™ Rough Valve Bodies

TU106508 Bath/Shower Trim Shown

GENERAL DESCRIPTION:

Double Ceramic Pressure Balance Cartridge: Features one-piece design with ceramic discs and ceramic balancing spool. Includes integrated check valves and hot limit safety stop. Cartridge capable of back to back capability. Ceramic balancing spool maintains constant output temperature in response to changes in relative hot and cold supply pressure. Washerless ceramic discs provide smooth handle movement and are unaffected by harsh water conditions.

Trim: Features 5" water-saving 3-function showerhead with a maximum 1.8 gpm/6.8 L/min. flow rate. Metal slip-on diverter spout. Metal wall valve trim with metal lever.

PRODUCT FEATURES

One-Piece Cartridge: Simplifies installation and maintenance.

Double Ceramic Pressure Balance Cartridge:

Combination of Ceramic Disc Mixing Valve and a Ceramic Balancing Spool in a one-piece cartridge.

Ceramic Disc Mixing Valve: Assures a lifetime of drip-free performance and smooth handle operation.

Ceramic Balancing Spool: Maintains a constant output temperature in response to changes in relative hot and cold supply pressure. Ceramic material is unaffected by mineral deposits and harsh water conditions.

Integrated Check Valves: Engineered to eliminate cross flow. Adjustable Hot Limit Safety Stop: Limits the amount of hot water allowed to mix with cold. Reduces the risk of accidental

Comfort Zone: Offers a wider shower range to fine tune the desired temperature within the useful temperature zone

Back-to-Back Capability: Hot and cold can be reversed quickly and easily.

Water Saving: Saves 28% water usage.

scalding.

2" TO 3" (51 TO 76 mm) 9-1/2 .1/2" NPT (223 mm) 3-3/4" (160 mm) OPTIONAL TO FINISHED FLOOR USUALLY BETWEEN 65" AND 78" (1651 AND 1981 mm) (127 mm) 7-3/81 (187 mm) 2-3/4" MAX. (69 mm) 1-3/4" MIN. (45 mm) 74" (1879 mm) FOR HEAD CLEARANCE 7-13/16" DIA. (198 mm) 4-1/8' (105 mm 18" (457 mm) OPTIONAL 7-5/8 (207 mm) 1-1/2" /2" COPPER OR SLIP-ON (177 mm) SPOUT TOP OF TUB RIM **BOTTOM OF TUB**

SUGGESTED SPECIFICATION

Bath/shower fitting shall feature water saving 3-function showerhead with Max. 1.8 gpm/6.8 L/min. flow rate. Shall feature double ceramic pressure balance cartridge. Cartridge is capable of back to back installation and shall feature integrated check valves to eliminate cross flow. Capable of meeting ASSE1016 @1.3gpm. Cartridge shall also feature hot limit safety stop. Fitting shall be: American Standard - Trim Kit Model # TU10650_. and Flash Valve Body Model # RU10

4/20 © 2020 AS America, Inc.



Patience®


Water-Saving Pressure Balance Bath/Shower Trim with Double Ceramic Pressure Balance Cartridge

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

ASSE 1016 / ASME A112.18.1016 / CSA B125.16 ASME A112.18.1 / CSA B125.1 Rated to meet ASSE 1016 @ 1.3gpm

CEC



			Finish Options			
* %	Product		Polished Chrome	Polished Nickel	Legacy Bronze	PVD Brushed Nickel
ΚΉ	Number	Description	002	013	278	295
TRIM	TU106508	Bath/Shower Trim Kit. Metal lever handle. Water-saving showerhead. Includes cartridge. LESS valve body.				
	TU106507	Shower Only Trim Kit. Metal lever handle. Water-saving showerhead. Includes cartridge. LESS valve body.				

* TRIM & ROUGH MUST BE ORDERED SEPARATELY.

DIES	Product Description	Without Screwdriver Stops	With Screwdriver Stops
B 0	Rough Valve Body. Universal* inlets/outlets.	RU101	RU101SS
ΛE	Rough Valve Body. Stub-out inlets/outlets for Press-Fit Fittings.	RU102	RU102SS
VAL	Rough Valve Body. PEX inlets/Universal outlets for Crimp Ring PEX system (ASTM F1807).	RU107	RU107SS
ИСН	Rough Valve Body. PEX Elbow inlets/Universal outlets for Crimp Ring PEX system (ASTM F1807).	RU107E	RU107ESS
™ RO	Rough Valve Body. PEX inlets/Universal outlets for Cold Expansion PEX system (ASTM F1960).	RU108	RU108SS
-lash	Rough Valve Body. PEX Elbow inlets/Universal outlets for Cold Expansion PEX system (ASTM F1960).	RU108E	RU108ESS
	Rough Valve Body. CPVC inlets/Universal outlets.	RU109	RU109SS

TIONAL	Product Number	Product Description Deep Rough-In Kit
95	M970649-YYY0A	Deen Rough-In Kit



Meets the American Disabilities Act Guidelines and **ANSI A117.1** Requirements for the physically challenged.

PART OF LIXIL

© 2020 AS America, Inc. 4/20