

AQUOR® RV CITY WATER INLET

Flush-mounted stainless steel hydrant with hose connector.

A reliable, leak-proof water outlet that can be used anywhere water access is needed, on land or sea.

Designed for pressurized water sources attached via hose. Installs vertically or horizontally. Can be used for incoming or outgoing water flow.

Rubber EPDM plug cover fits snugly into outlet, sealing out any dirt or debris when not in use.



- Valve opens when hose connector is inserted.
- High-performance Viton® O-rings ensure a reliable leak-proof seal, even in harsh conditions.
- Stainless steel body and pressure-closed valve provide zero-maintenance reliability for years.
- 316L alloy is marine-grade and highly resistant to corrosion.
- Crush-proof acetal resin hose connector rated for 150,000 cycles and 200 lbs of lateral force. Attach to any garden hose.
- Durable EPDM plug cover seals outlet when not in use.
- Hydrant can be mounted vertically or horizontally.
- Hydrant comes standard with 1/2" female NPT inlet. Optional 90° elbow and PEX inlets also available.
- Each hydrant kit comes furnished with one hose connector.
- Any 3/4" accessory (eg. timers, splitters, ball valves) can be attached to end of hose connector.
- Hydrant will provide mild freeze protection if disconnected and allowed to drain fully.
- To reverse hose threads for incoming water, use our Double-Female Adapter (FA-4).



Kit includes 1x hose connector (CN-F).

TECHNICAL INFO

- Inlet: 1/2" NPT
- Outlet: 3/4" Garden Hose Thread (male)
- Flow rate: 6.8 GPM @ 52 PSI
- Operating water pressure: 25 - 125 PSI
- Operating temperature range: 0° - 140° F
- Warranty: 10-year stainless components, 5-year polymer

DW-5

4/21

