

**Certifications Standards**

ASME A112.18.1 / CSA B125.1

CEC**Finition seule pour robinet de bain au sol avec douchette****Caractéristiques**

- Bec de bain : 45,3 l/min (12 gpm) - 60 psi
- Inverseur de type bouton poussoir intégré au bec de bain
- Douchette : max : 6,6 l/min (1.75 gpm) - 80 psi
- Douchette en laiton ne conduisant pas la chaleur
- Support de douchette inclinable
- Crochet intégré au support de douchette
- Boyau en PVC fini KK ou en laiton pour les autres finis
- Commandez UN des bruts suivants pour compléter la finition :
- ROU-110C-00-B
- ROU-110W-00-B

Finis disponibles

- CC : Chrome
- KK : Noir mat
- LL : Laiton satiné
- MM : Or ambré
- BB : Blanc
- NN : Nickel brossé
- YY : Nickel poli
- VV : Cuivre satiné
- TT : Bronze vénitien
- KM : Noir titane
- GG : Or

FR**Trim only for floor-mounted tub filler with hand shower****Features**

- Bath spout: 12 gpm (45,3 l/min) - 60 psi
- Tub spout with integrated push-button diverter
- Hand shower: max: 1.75 gpm (6,6 l/min) - 80 psi
- Non-conductive brass hand shower
- Reclining hand shower holder
- Built-in hook on the hand shower holder
- PVC hose in KK finish or brass for other finishes
- Order ONE of the following rough-in to complete the trim:
- ROU-110C-00-B
- ROU-110W-00-B

Available finishes

- CC: Chrome
- KK: Matte black
- LL: Satin brass
- MM: Warm gold
- BB: White
- NN: Brushed nickel
- YY: Polished nickel
- VV: Satin copper
- TT: Venitian bronze
- KM: Black titanium
- GG: Gold

EN