Cat. No.

ATFRECN67IG-XX





L: 67" W: 30-½" H: 23-¾"

Water depth: 17-3/8" to top of tub Water depth: 14-1/4" to OF Overflow slot lenght: 2-1/2" Center drain to back of rim: 15" Bottom of drain to floor: 4-7/8" Bathing well to floor: 5-3/4"

The following is recommended for ATFRECN67 tubs:

•Faucets: part #7901 or 7913



For easier installation we recommend use of 5598-ITD Easy Install Rough In Kit

Gallon Capacity with OF: 44
Shipping Weight: 142 lbs.
Empty Weight: 82 lbs.
Filled Weight with OF: 450 lbs.

Features:


- ► Interior and exterior walls acrylic sheets
- ▶ Drain and overflow covers included (available in 7 finishes)
- ► Rim is 1-1/2" wide
- ► Overflow slot with integrated drain
- ▶ Drain included
- ► No faucet holes
- ► Angle slope of tub: 20°
- ► Includes built-in adjusters
- ► Tub is thoroughly inspected before shipment
- ▶ Option to add foam insulation between tub walls available
- ► Not compatible with air jet system


Finishes:


CP Polished Chrome
PB Polished Brass
PN Polished Nickel
BN Brushed Nickel
ORB Oil Rubbed Bronze

WT White
MB Matte Black

Custom Colors Available (inside of tub is always white enamel): Painted bathtubs are considered "special order" and are not returnable \$160 Bisque or Black \$250 Designer Color







Dimensions of fixture are nominal and specifications subject to change without notice.