Cat. No. ATOVN63IIG-XX





L: 62-1/4" W: 29-1/2" H: 22-1/2"

Water depth: 17" to top of tub Water depth: 14" to overflow Overflow slot lenght: 2-1/2"

Center drain to back of rim: 14-3/4"

Bottom of drain to floor: 4" Bathing well to floor: 4-3/4"

The following is recommended for ATOVN63I tubs:


- •Faucets: part #4602, 4604 or 7082
- •Rigid, freestanding supplies: part #4502

Gallon Capacity with OF: 51
Shipping Weight: 140 lbs.
Empty Weight: 80 lbs.
Filled Weight with OF: 530 lbs.



For easier installation we recommend use of 5598-ITD Easy Install Rough In Kit





(Air jet configuration if system is added, more info on page 2.)

Features:


- ► Interior and exterior walls acrylic sheets
- ▶ Drain and overflow covers included (available in 7 finishes)
- ► Tub rim is 1-1/2" wide
- ► No faucet holes
- ► Overflow slot with integrated drain
- ▶ Drain included
- ► Angle slope of tub: 29°
- ► Includes built-in adjusters
- ► Tub is thoroughly inspected before shipment
- ▶ Option to add foam insulation between tub walls available
- ▶ New: Air jet system now available, more info on page 2


Finishes:


CP Polished Chrome
PB Polished Brass
PN Polished Nickel
BN Brushed Nickel
ORB Oil Rubbed Bronze

WT White MB Matte Black

Custom Colors Available (inside of tub is always white enamel): Painted bathtubs are considered "special order" and are not returnable \$160 Bisque or Black \$250 Designer Color







Dimensions of fixture are nominal and specifications subject to change without notice.

Cat. No. AIR KIT 1, AIR KIT 2





- A AIR JET Bottom air jets for maximum bubble action.
- B BLOWER The heart of the massage system.
- C MANIFOLD Double back flow security prevention device.
- D FLEXIBLE PVC HOSING IAPMQ certified.
- E MAIN AIR INTAKE HOSE High temperature and pressure resistant.

Air Kit is installed in tub before shipment

Features:

- ▶ 750 Watt blower motor operates system
- ▶300 Watt air heater warms air
- ► System powered by 120V
- ▶ 16 brass air jets placed in bottom of tub
- ► Each air jet has 24 holes
- ► Air jet caps available in white (AIR KIT 1) or black (AIR KIT 2)
- ► Includes 1¼" x 3' main air hose plus 1¼" x 9' extension hose
- ► Automatic system purge after each use
- ► Automatic safety timer turns off system after 20 minutes
- ► Includes water tight remote control
- ► Compatible with most acrylic, copper and resin tubs with no feet
- ► Not available with cast iron tubs or tubs with feet

