

*For Residential and Commercial Applications*

Job Name		Engineer / Architect	
Job Location		Wholesaler	
Submittal Date		Contractor	

## BWB05/08 .57” ID Braided Water Heater Connectors


**Use:** For use in exposed locations only to connect water heaters and other water connected devices to the water supply. Not intended for use with recirculating water systems that produce continuous use temperatures above 115° F. For those applications use our CopperFlex™ series connectors.

**Design Features:**

- **Corrosion resistance** to harsh chemicals found in common household cleaning and plumbing repair products
- **Strong and flexible.** The polymer braid exhibits greater elasticity than stainless steel braiding, significantly increasing the flexibility of the connector
- **No kinking, no crimping.** The polymer braided jacket is specially engineered to bend freely without kinking or crimping the connector
- **Won't work harden** even with repeated bending
- **No dielectric union needed** with installation as the braiding and rubber are constructed of non-conductive materials
- **Nut provides a full thread engagement** resulting in a secure connection
- 

**Operating Specifications:**

**Temperature:** 40° to 160° F, intermittent to 180° F  
**Pressure:** water pressures up to 125 PSI maximum




CONNECTOR MATERIAL SPECIFICATIONS	
Inner Hose	EPDM rubber
Braiding	PVC coated polyester yarn
Barb	Compliant brass
Ferrule	C26000 brass
Nut	C36000 brass
Washer	Nitrile rubber
Compression Ring	C36000 brass

*This specification and all information contained herein is the confidential and exclusive property of Brasscraft Manufacturing Company and shall not be disclosed to others without the written consent of Brasscraft Mfg. Co. This specification must be returned to Brasscraft Mfg. Co. if requested.*

# BWB05/08 .57" ID Braided Water Heater Connectors

**Part Listing:**

- BWB05-18 .57" ID X 18" connector with 3/4" FIP x 5/8" OD Compression end fittings
- BWB08-12 .57" ID X 12" connector with 3/4" FIP x 7/8" OD Compression end fittings
- BWB08-15 .57" ID X 15" connector with 3/4" FIP x 7/8" OD Compression end fittings
- BWB08-18 .57" ID X 18" connector with 3/4" FIP x 7/8" OD Compression end fittings
- BWB08-24 .57" ID X 24" connector with 3/4" FIP x 7/8" OD Compression end fittings
- BWB08-24 X .57" ID X 24" connector with 3/4" FIP x 7/8" OD Compression end fittings, cut case



<b>PART DIMENSIONS (Inches)</b>					
<b>Connector Length – Nut by Nut</b>					
<b>Model</b>	<b>Dim.</b>	<b>12"</b>	<b>15"</b>	<b>18"</b>	<b>24"</b>
BWB05	A	----	----	18.00 / 19.00	----
BWB08	A	12.00 / 13.00	15.00 / 16.00	18.00 / 19.00	24.00 / 25.00

**Listings & Certifications:**

- IAPMO listed to ASME A112.18.6 / CSA B125.6 (includes NSF/ANSI372 and NSF61)



*This specification and all information contained herein is the confidential and exclusive property of Brasscraft Manufacturing Company and shall not be disclosed to others without the written consent of Brasscraft Mfg. Co. This specification must be returned to Brasscraft Mfg. Co. if requested.*