

For Residential and Commercial Applications

Job Name		Engineer / Architect	
Job Location		Wholesaler	
Submittal Date		Contractor	

CEPX19X Multi Turn Angle Stop - Cold Expansion Barb (for PEX) x Compression

Use: For use in potable water distribution systems in accessible locations only. Not intended for recirculating water systems that produce continuous use temperatures above 115° F. For those applications, use our KT™ series ball stop.

Design Features:

- **Machined, one-piece brass body** provides strength, durability, and long-lasting performance
- **Easy-to-remove handle** with screw attachment helps protect against accidental operation during rough-ins
- **PEX end** designed to ASTM F1960
- **For use with** ASTM F876 PEX tubing, in ASTM F877 water distribution systems
- **DESIGNED, MACHINED AND ASSEMBLED IN THE USA**

Operating Specifications:

Temperature: 40° - 140° F
Pressure: 125 PSI maximum

STOP MATERIAL SPECIFICATIONS	
Body	Brass, plated
Stem	POM
Bib & Packing Washer	Rubber
Handle	ABS, plated or polycarbonate
Handle Screw	Steel, zinc plated
Compression Nut	Brass, plated
Packing Nut	Brass, plated
Compression Sleeve	Brass

PART DIMENSIONS (Inches)		
Model	DIM. A	DIM. B
CEPX19X	.93	2.69
CEPX19L1X	.74	2.69

Part Listing:

- CEPX19X C 1/2" nom cold expansion barb (for PEX) inlet x 3/8" OD compression, chrome
- CEPX19L1X CB 1/2" nom cold expansion barb (for PEX) inlet x 3/8" OD compression, chrome, less nut and sleeve, bulk

Listings & Certifications:

- IAPMO listed to ASME A112.18.1 / CSA B125.1 (includes NSF/ANSI372 & NSF61)

This specification and all information contained herein is the confidential and exclusive property of Brasscraft Manufacturing Company and shall not be disclosed to others without the written consent of Brasscraft Mfg. Co. This specification must be returned to Brasscraft Mfg. Co. if requested.

