# For Residential and Commercial Applications

Job Name	Engineer / Architect	
Job Location	Wholesaler	
Submittal Date	Contractor	

# G2QPS14X 1/4 Turn Push Connect Straight Stop - Push Connect Outlet

**Use:** For use in potable water distribution systems in accessible locations only. Not intended for recirculation systems/continuous use temperatures above 115° F. For those applications, use our KT<sup>™</sup> series ball stop.

#### **Design Features:**

- Compatible with PEX, copper, and CPVC
- Easy-to-remove handle helps protect against accidental stop operation during rough-ins
- Pre-inserted tube stiffener is "installation ready" for a faster connection
- Compact machined one-piece brass body design
- Fast, reliable, and secure connection
- Push connect x push connect inlet and outlet
- Smooth 1/4 turn operation
- 100% leak tested
- . Ø

## **Operating Specifications:**

**Temperature:** 40° - 160° F **Pressure:** 125 PSI maximum

STOP MATERIAL SPECIFICATIONS				
Body	Brass, plated			
Handle	ABS, plated or zinc die cast, plated			
Handle Screw	Steel, zinc plated			
O-ring	Rubber			
Stem Shaft	Polypropylene			
Stem Barrel	TPE			
Removal Flange	Polypropylene			
Tube Support	POM			
Gripper Ring	Stainless steel			
Push Connect O-ring	EPDM			


### Part Listing:

G2QPS14X C 1/2" nom push connect x 3/8" OD push connect, chrome plated

#### **Listings & Certifications:**

IAPMO listed to ASME A112.18.1 / CSA B125.1





<b>←</b>	В ———	<b>→</b>

PART DIMENSIONS (Inches)			
Model	DIM. A	DIM. B	
G2QPS14X	1.03	2.74	



This specification and all information contained herein is the confidential and exclusive property of Brasscraft Manufacturing Company and shall not be disclosed to others without the written consent of Brasscraft Mfg. Co. This specification must be returned to Brasscraft Mfg. Co. if requested.

(includes NSF/ANSI 372 and NSF61)