## For Residential and Commercial Applications

Job Name	Engineer / Architect	
Job Location	Wholesaler	
Submittal Date	Contractor	

# V1-\*\*DW Speedi Plumb® Vinyl Dishwasher Connector - Compression Inlet

Use: For use in potable water distribution systems in accessible locations only

#### **Design Features:**

- No kink hose. The specially engineered reinforced PVC hose provides unique flexibility to prevent kinking and crimping
- Strong & durable with a tighter weave and two-layer bonded construction, outperforms conventional vinyl connectors
- Longer wing nuts ease installation for speedier connections
- Nitrile rubber washers provide a large pliable sealing surface and ensures a long lasting water tight connection
- 8-sided pneumatic crimp provides greater dependability for reliable nut-to-hose connections



### **Operating Specifications:**

**Temperature:** 40°-160° F, intermittent to 180° F

Pressure: 125 PSI maximum


**Tubing Diameter:** 0.300" ID (0.500" OD)




CONNECTOR MATERIAL SPECIFICATIONS			
Hose	PVC with polyester braid reinforcement		
Barb	Brass		
Ferrule	Steel, zinc plated		
Nut	Brass, plated		
Washer	Rubber		
Compression Nut	Brass, plated		
Compression Ring	Brass		

#### Part Listing:

V1-120DW F 3/8" compression x 3/8" compression x 9" length



# V1-\*\*DW Speedi Plumb® Vinyl Dishwasher Connectors - Compression Inlet



PART DIMENSIONS (Inches)		
Model	DIM. A	
V1-120DW	120.0 / 121.0	

### **Listings & Certifications:**

 IAPMO listed to ASME A112.18.6 and CSA B125.6 (includes NSF/ANSI372 and NSF61)







This specification and all information contained herein is the confidential and exclusive property of Brasscraft Manufacturing Company and shall not be disclosed to others without the written consent of Brasscraft Mfg. Co. This specification must be returned to Brasscraft Mfg. Co. if requested.

