For Residential and Commercial Applications

Job Name	Engineer / Architect	
Job Location	Wholesaler	
Submittal Date	Contractor	

WC43 7/8" OD Copper Water Heater Connectors – Female Sweat x Male Sweat

Use: For use in exposed locations only to connect water heaters and other water connected devices to the water supply.

Design Features:

. 0

Operating Specifications:

Temperature: 40° to 180° F (NSF61 maximum 82° C) **Pressure:** water pressures up to 125 PSI maximum

	ACHINED AND	
ED, A	PSS PSS	
SIGN	MBL	
A P	8	
	" THE USP	

CONNECTOR MATERIAL SPECIFICATIONS		
Tubing	Copper	
Plug / Cap	Plastic	

PART DIMENSIONS (Inches)					
Connector Length (±.25)					
Model	Dim.	12"	15"	18"	24"
WC43	Α	11.25	14.25	17.25	23.25

Part Listing:

Ш	WC45-12	3/4 Horn remaie sweat (7/6 Hz) x 3/4 Horn male sweat (7/6 Hz) x 12 Herigin
	WC43-15	3/4" nom female sweat (7/8" ID) x 3/4" nom male sweat (7/8" OD) x 15" length
	WC43-18	3/4" nom female sweat (7/8" ID) x 3/4" nom male sweat (7/8" OD) x 18" length
	WC43-24	3/4" nom female sweat (7/8" ID) x 3/4" nom male sweat (7/8" OD) x 24" length

Listings & Certifications:

IAPMO listed to ASME A112.18.6 / CSA B125.6



