



Unbreakable, bright annealed stainless steel mirror:

Model 7481-XXXX (Specify width and height)

Product Materials

MIRROR: 20 gauge bright annealed stainless steel. Material is stretcher-leveled for uniformity. Surface is bright and smooth with mirror-like finish. A 1/4" return conceals backing.

BACKING: tempered Masonite bonded to mirror with adhesive.

Stainless steel mirrors will differ in optic quality from glass mirrors.

Installation

Verify all rough-in dimensions prior to installation. Secure to wall with tamper-resistant mounting screws (included) at holes provided. Provide in-wall backing at mounting screw locations.

Guide Specification

Mirror shall be fabricated of bright annealed stainless steel with smooth reflective finish. Unit shall have 1/4" return to conceal 1/4" tempered Masonite backing bonded to mirror with adhesive. If either the width or height exceed 24", an additional hole will be added on each side.

Stainless Steel Mirror shall be Bradley Model 7481-_____ " W x _____ " H (specify width and height).

Model 7481 series stainless steel mirrors can be fabricated to a maximum size of 47"W x 72"H.

In larger sizes, these units are subject to distortion and/or "oil canning" for which Bradley Corporation cannot accept responsibility.

ADA Compliant

- Consult local and national accessibility codes for proper installation guidelines.
- Conformity and compliance to local and national codes is the responsibility of the installer.

Dim. "A" Key Surface:	For Dim. "A"	Bottom of Unit
Mirror's bottom edge of the reflecting surface to finished floor	40" (1016mm)	40" (1016mm)
	37" (940mm)	37" (940mm)
	34" (864mm)	34" (864mm)
Rough wall opening:		
Surface Mount:	No rough wall opening, see overall dimensions	

