

All brass construction

25+ artisan finishes including 12 PVD finishes

Features



Widespread Lavatory Faucet

3802 3802T

3802X

1/4 turn ceramic disc cartridge(s) 3802XT Flexible braided hoses for ease of installation ϕ 1-1/4" all brass touch style pop up drain assembly 1.2gpm (4.5 L/min) max flow rate **Codes/Standards Applicable** AsterSen. Product meets or exceeds the following: ASME A112.18.1/CSA B125.1 NSF 61, NSF 372, CEC & DOE EPA WaterSense 3802-SN shown Commonwealth of MA ADA compliant (lever handles only) 8" minimum [203] 6-11/16' [169] 5-5/16" [134] 6-3/4" [171] 2-7/16" 63 3-11/16" [93] 2 [51] Ø2' 1-1/16" [27] min stem height [51] for all handles 9/16' 2-1/16" [53] max [14] 2-15/16" max (2-13/16" [72] less spacer) [75] 4-3/4" [121] 2x 3/8" compression fittings Ø2-3/16" [56] 1/2" NPT 2-7/16" 2-1/8th max Ø2" 63 [54] 51 1-13/16' [46] 6-5/16" [160] Through-Hole Specifications <u>Min</u> Recommended Ø11/16" [18] Ø1-1/8" [29] Ø1-1/2" [38] Spout:

Specifications subject to change without notice

www.californiafaucets.com

3802X handle

Ø1-1/4"

32

Valve:

Ø1-1/4" [32]

3802 sp 231002 CC I am approving this document

Ø1-3/8" [35]

Dimensions are inches, rounded to 1/16"

[Dimensions in brackets are mm, rounded to 1mm]

<u>Max</u>

Ø1-1/2" [38]