

25+ artisan finishes including 12 PVD finishes

Features



Widespread Lavatory Faucet

4002 4002X

CC I am approving this document

All brass construction 1/4 turn ceramic disc cartridge(s) Flexible braided hoses for ease of installation ϕ 1-1/4" all brass touch style pop up drain assembly 1.2gpm (4.5 L/min) max flow rate aterSen **Codes/Standards Applicable** 4002 shown Product meets or exceeds the following: ASME A112.18.1/CSA B125.1 NSF 61, NSF 372, CEC & DOE EPA WaterSense Commonwealth of MA ADA compliant (blade lever handle only) 4002X 8" minimum [203] 6-7/8" [174] 5-7/16" [139] 2-3/16" [55] 3-3/16" [81] 2-1/4" 23 [57] 1-7/16" 1-1/16" [27] min stem height 3x Ø2" [37] [51] for all handles 2-1/8 max 9/16" min [54] [14] 3" max (2-9/16" [66] less spacer) [77] 4-3/4" [121] 0 0 1/2" NP Ø2-3/16" 2x 3/8" compression fittings [56] 2-1/8["] max 2-1/2" Ø2" [54] 64 [51] 2-1/4 **Through-Hole Specifications** 57 Min Recommended Max Ø1-1/8" [29] Ø1-1/2" [38] Spout: Ø11/16" [18] 6-5/16" Ø1-1/4" Ø1-3/8" [35] Ø1-1/2" [38] Ø1-1/4" [32] Valve: 4002X handle [160] [32] Dimensions are inches, rounded to 1/16" Specifications subject to change without notice [Dimensions in brackets are mm, rounded to 1mm] www.californiafaucets.com Page 1 4002 sp 240603