


CF-K10-102-XX

Features

- 360° rotating spout with pull down sprayer
- Magnetic docking secures sprayhead into spout
- One button brass spray head has dual function aerated or spray mode
- Spray jets have easy-to-clean surface that withstand mineral build-up
- Quiet polymer-braided hose with rotating joint at sprayhead allows for smooth and non-binding use
- Ceramic disc cartridge
- Max flow rate: 1.8 gpm
- Solid brass construction
- Over 30 finishes including 15 PVD finishes



CF-K10-102-42 shown

XX = DENOTES HANDLE STYLE

Codes/Standards

- Meets or exceeds the following:
- ASME A112.18.1/CSA B125.1
 - NSF 61 and NSF 372
 - CEC/DOE
 - ADA compliant

DIMENSIONS (in.)			
XX HANDLE	A	B	C
33	7 1/2	4 1/8	3 13/16
35	7 1/2	4 1/8	3 13/16
40	7 1/4	4	3 5/8
42	7 7/8	3 15/16	3 9/16
55	7 1/4	4	3 5/8
64	7 7/16	4 1/16	3 7/8
CLEV	7 9/16	3 3/16	3 15/16

THROUGH-HOLE SPECIFICATIONS		
MIN	RECOMENDED	MAX
Ø 1-1/4"	Ø 1-3/8"	Ø 1-3/8"

