

# caroma®

Date: Feb 2018

Supersedes all previous issues

## Sydney Smart II One Piece Easy Height Elongated with Side Lever

### #987200

1.28/0.8 gpf (4.8/3 lpf) Water Saving Dual Flush High Efficiency Toilet (HET)

One-Piece Ultra Low Flush (ULF) Vitreous China Washdown Toilet



**Sydney Smart II One Piece  
Easy Height Elongated  
1.28/0.8 gpf (4.8/3L)  
Dual Flush HET  
#987200**

**One Piece Ultra Low Flush (ULF)  
Vitreous China Washdown Toilet**



A modern concept one piece toilet featuring a **1.28/0.8 gpf (4.8/3 lpf)** flush volume. **Sydney Smart II One Piece Easy Height Elongated** left or right lever dual flush high efficiency toilet (HET) is designed to provide a seat height of 17-1/2" (445mm) measured to the top of the toilet seat. The versatility of the **Sydney Smart II One Piece Easy Height Elongated** toilet makes it ideal for able bodied, ambulant persons with disabilities or for wheelchair users. Designed with smooth rounded contours and a concealed outlet for easy cleaning.

**Important:** The Sydney Smart II One Piece Easy Height Elongated toilet will comply with the Americans with Disabilities Act when installed to Easy Height Standards for Accessible Design, Section 4.16 Water Closets. Further reference must be made to the relevant sections of Easy Height Standards for Accessible Design with current amendments to determine clear floor space, grab bar, and operation requirements.

- Toilet:** Sydney Smart II One Piece Easy Height Elongated 1.28/0.8 gpf (4.8/3 lpf) dual flush box rim.
- Outlet:** Floor mounted suitable for connection to waste outlet with offset plastic outlet connector for 10" (255mm) to 12" (305mm) rough-in.
- Tank:** The tank is an integral part of the toilet with a free fitting lid and is suitable for domestic and light commercial applications. Push down side lever for full flush (1.28 gpf / 4.8 lpf) and pull up side lever for reduced flush (0.8 gpf / 3 lpf). Tank with a right hand lever is available.
- Water Control Valve:** **Standard Bottom Entry** -- available as left hand inlet which incorporates a super quiet water control assembly. Internal overflow only.
- Weight:** 103 lbs (47.0 kg).
- Fixing:** The one piece toilet is fixed to the floor with corrosion resistant screws and closet bowl guard washers and a fixing assembly kit. Bowl is to be bonded to the floor with an approved silicon caulking.
- Seat:** The soft close detachable elongated seat is included: Code No. 326611W
- Colors:** White.
- Dimensions:** All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

Top view dimensions: 7-1/2" (185mm) tank width, 13-1/16" (20mm) tank depth, 5-1/2" (140mm) seat width, 18-1/2" (470mm) seat length, 14-1/8" (360mm) bowl width, 29-15/16" (760mm) total height, 21-1/4" (540mm) bowl depth.

Side view dimensions: 10-3/4" (272mm) tank width, 21-1/4" (540mm) bowl depth.

Front view dimensions: 16-1/2" (420mm) seat height, 30-3/8" (770mm) approx. total height.

Bottom view dimensions: 3/4" (20mm) tank depth, 11" (280mm) bowl width, 10" (255mm) rough-in, 12" (305mm) rough-in.

**Sydney Smart II One Piece  
Easy Height Elongated Toilet:**

		Code No.
LH Lever	LH inlet	987200
RH Lever	LH inlet	987200-R

MaP 1000g

Meets EPA Criteria  
Certified by IAPMO R&T

HIGH EFFICIENCY TOILET  
**HET**

**Note:** All height dimensions to underside of closet bowl. Make allowance for bedding.

**Closest bowl fixing:** The closet bowl should be bedded with an approved silicon caulking.