ACCESSORIES AND PARTS 1020-035KJKABNF



Product Type

2.5 GPM (9.5 L/min) Spout Flow Control Assembly

Features & Specifications

- Designed for Gooseneck Spouts
- Installs into Inlet of Spout for Added Vandal Resistance
- Simple Installation and Replacement
- Can Convert Existing Spouts to Flow Control Insert Design
- Insert Allows for Control of Flow Rate without the need of an traditional outlet
- Mutiple Inserts are Available for a Wide Flow Variety
- ECAST® design provides durable construction with total lead content equal to or less than 0.25% by weighted average

Job Name	
Item Number	
Section/Tag	
Model Specified	
Architect	
Engineer	
Contractor	
[] Submitted as Shown	[] Submitted with Variations
Date	



ECAST

ECAST products are intended for installation where state laws and local codes mandate lead content levels or in any location where lead content is a concern.

1020-035KJKABNF



Architect/Engineer Specification

Operation and Maintenance

Installation should be in accordance with local plumbing codes. Flush all pipes thoroughly before installation. After installation, remove spout outlet or flow control and flush faucet thoroughly to clear any debris. Care should be taken when cleaning the product. Do not use abrasive cleaners, chemicals or solvents as they can result in surface damage. Use mild soap and warm water for cleaning and protecting the life of Chicago Faucet products. For specific operation and maintenance refer to the installation instructions and repair parts documents that are located at www.chicagofaucets.com.

Chicago Faucets, member of the Geberit Group, is the leading brand of commercial faucets and fittings in the United States, offering a complete range of products for schools, laboratories, hospitals, office buildings, food service, airports and sport facilities. Call 1.800.TECTRUE or 1.847.803.5000 Option 1 for installation or other technical assistance.

