

MECHANICAL FAUCETS

830-PVDF

Pure Water Faucets



Product Type

Deck Mounted PVDF PVDF Pure Water Faucet

Features & Specifications

- PVDF
- Inlet x Outlet 3/8" NPT Female Thread
- All virgin natural PTFE wetted fluid path
- Needle valve activation at point of use
- Simplified installation of recirculation module
- All components designed for extreme industrial environments
- FDA, USDA, and USP standards are either met and/or exceeded
- Ultra smooth internal flow path
- Unique heavy wall construction
- Control valve offers easy open / close valve, 120 degree rotation full flow to closed
- PTFE sealed, encapsulated PTFE shut off seal for unlimited life
- Black handle with white marker and black "DI" text per SEFA code recommended practice No. 7 for DI Water Applications
- Control valve is completely renewable by replacing the internal cartridge, per SEFA 7-2010-8.2a
- Positive stop at off position
- Exceptional low torque on/off operation
- Recirculating Laboratory Faucet designed to provide a continual fluid flow to the point of use to eliminate the inherent dead leg.

Performance Specification

- Rated Operating Pressure: 150 PSI

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Job Name _____

Item Number _____

Section/Tag _____

Model Specified _____

Architect _____

Engineer _____

Contractor _____

Submitted as Shown

Submitted with Variations

Date _____



2100 South Clearwater Drive
Des Plaines, IL
P: 847/803-5000
F: 847/803-5454
Technical: 800/TEC-TRUE
www.chicagofaucets.com

