

Tub and Shower Fittings

Product Type

Wall Mounted Pressure Balancing Pressure Balancing Tub and Shower Valve with Shower Head

Features & Specifications

- Pressure Balancing
- Pressure Balancing Tub and Shower Valve Only
- 2.5 GPM Max. Flow Rate @ 80 PSI Shower Head
- Pressure Balancing Valve Cartridge
- 1/2" Nominal Copper and 1/2" NPT Hot and Cold Supply Inlets and Outlets
- Includes Shower Head Arm and Wall Flange
- Shower Valve Cycles from Cold to Hot
- Embossed and Color Coded Indexing on Wall Plate
- Integral Service Stops with Checks to Prevent Cross Flow
- Diverter Valve with Indexed Wall Flange Designed to Alternate between Shower Head and Hand Spray
- Wall Elbow with In-Line Vacuum Breaker
- 1.5 GPM Hand Spray with 59" Stainless Steel Hose and Pause Control
- 36" Wall Mounted ADA Grab Bar with Hand Spray Holder

Performance Specification

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-120°F

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Codes & Standards

- ASME A112.18.1/CSA B125.1
- ASSE 1016
- ADA ANSI/ICC A117.1

Job Name _____

Item Number _____

Section/Tag _____

Model Specified _____

Architect _____

Engineer _____

Contractor _____

☐ Submitted as Shown ☐ Submitted with Variations

Date _____



Architect/Engineer Specification

Technical drawings of the back view of a valve assembly, showing dimensions and component labels.

Left Side View:

- Top view: $\varnothing 2-1/2$ [64] FLANGE
- Side view: $9-5/8$ [244] (overall height), $3-1/8$ [79] (flange thickness)
- Bottom view: ALL DOTTED LINE PIPING SUPPLIED BY OTHERS
- Side view: $1-1/2$ [38] MIN. / $2-1/4$ [57] MAX. (valve body height)
- Bottom view: $\varnothing 6-3/4$ [171] (base diameter)
- Side view: $1/2$ [13] (valve body height)
- Bottom view: $6-3/8$ [162] (base width), $3-1/4$ [83] (base width), $\varnothing 5-7/8$ [149] ROUGH-IN GUIDE
- Side view: $1/2$ NPT MALE THREAD (top), $1/2$ NPT MALE THREAD OR $1/2$ NOMINAL COPPER SWEAT (4 PLACES) (bottom)
- Bottom view: 78 [188] APPROX. TO FINISHED FLOOR
- Side view: $1/2$ NPT FEMALE INLET
- Bottom view: TUB OUTLET TO BE PLUGGED (PLUG BY OTHERS)

Back View of Valve Only:

- Top view: $\varnothing 3-1/8$ [79] (top flange)
- Side view: 2 [51] (valve body height)
- Bottom view: $\varnothing 3-1/8$ [79] (bottom flange)
- Side view: AS REQUIRED (valve body height)

Right Side View:

- Top view: $2-1/4$ [57] (valve body height)
- Side view: $1/2$ NPT FEMALE INLET
- Bottom view: $\varnothing 2-1/8$ [54] (valve body height)
- Side view: BACKFLOW PREVENTER
- Bottom view: AS REQUIRED (valve body height)

Last Revision: 07/16/2018 • Date Printed: 02/4/2019 • Product specifications subject to change without notice