

Pre-Rinse Faucets

CER-TECK® 203mm (8") Center Wallmount Base Faucet

Model No: 55C1583-S8

COMPLIES WITH:

- CSA certified.
- Complies to ASME A112.18.1/CSA B125.1
- For commercial use only
- Verified compliant with 0.25% weighted average Pb content regulations
- (Contact Delta Representative for State and/or Local Approvals)



SPECIFICATION:

- 203mm(8") center two handle WALLMOUNT pre-rinse faucet
- $_{\bullet}$ Cast brass body with integral check stops to prevent crossflow
- Centers adjustable from 7.75" to 8.25" unless AC option selected
- Polish chrome plated finish
- CER-TECK® ceramic structures
- Flowrate w/ Standard Pre-Rinse Spray Outlet 1.05 GPM @ 60 PSI
- Spout: S8 356mm (14") Tubular Swing Spout(S8)
- Handle#: 3 76 mm (3") Lever Blade Handles-ADA Compliant-Metal-Color indexed-Vandal Resistant screws
- Self Close Pre-Rinse Spray with spring loaded stainless steel hose, add-on faucet with standard 8" tubular spout and 1.5 USGPM (5.7 L/min) aerator


OPERATION:

Not Available

(Dimensional drawing on following page)

Delta reserves the right (1) to make changes to specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference. Measurement may vary plus or minus 6mm(0.25"). Mounting locations are suggested only. Check with local codes for requirements in your area. This spec was produced April 13, 2021.





Delta reserves the right (1) to make changes to specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference. Measurement may vary plus or minus 6mm(0.25"). Mounting locations are suggested only. Check with local codes for requirements in your area. This spec was produced April 13, 2021.