

Hose Cocks

Single ball valve assembled in deckmount turretassembled shank

brass locknut

raised lockwasher for positive grip-- vandal resistant locking pins on turret(can be removed in field if not required)

Model No: W6210VAC

COMPLIES WITH:

- Lindicates compliance to ICC/ANSI A117.1
- Not for potable water.
- (Contact Delta Representative for State and/or Local Approvals)



SPECIFICATION:

- Ball valve hose cock(s)
- Floating ball-type design
- Universal 10 serration vandal resistant nozzle with 3.2mm(1/8") outlet removable with flat on one side
- Forged brass non-removable vandal resistant handle (ADA compliant) obvious on/off positions
- O-ring seals
- Maintenance free- no need to regrease sealing surfaces or take valve apart
- 10 year warranty-every ball valve carries its date of manufacture on the underside of the body
- Life cycle tested to up to 100,000 cycles
- Single ball valve assembled in deckmount turret-assembled shank,brass locknut, raised lockwasher for positive grip-- vandal resistant locking pins on turret(can be removed in field if not required)
- Chrome Finish
- Assembled Shank: Shank (L)
- Overall length 4.44" [was SH1](2.84" exposed)
- Indexed For: VAC Vacuum(Yellow)
- Use of this ball valve requires special clamping procedures by others
- Vacuum valves supplied with corrosion resistant ball and viton o'rings for improved durability
- Cannot be converted to any other valve.
- Shank With 1/4" IP tailpiece and coupling nut(Standard)


OPERATION:

Not Available

(Dimensional drawing on following page)

Delta reserves the right (1) to make changes to specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference. Measurement may vary plus or minus 6mm(0.25"). Mounting locations are suggested only. Check with local codes for requirements in your area. This spec was produced May 21, 2021.





Delta reserves the right (1) to make changes to specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference. Measurement may vary plus or minus 6mm(0.25"). Mounting locations are suggested only. Check with local codes for requirements in your area. This spec was produced May 21, 2021.