




Vero Air Toilet wall-mounted Duravit Rimless for SensoWash® ♿
 # 252559..92 / 252559..92

< 14 5/8" Inch >



Toilet wall-mounted Duravit Rimless for SensoWash®	Dimension	Weight	Order number
rimless, washdown model, Durafix included, only in combination with SensoWash, connecting elements for SensoWash with concealed connections included, cUPC® listed*			
Colors			
00 White 20 HygieneGlaze (an antibacterial ceramic glaze that provides almost indefinite effectiveness)			
Variant			
♣ 1.6/0.8 gpf	14 5/8" x 22 1/2" Inch	55.8 lb	252559..92
♣ 1.6/0.8 gpf	14 5/8" x 22 1/2" Inch	55.8 lb	252559..92
Infobox			
Wall-mounted toilet is ADA compliant, when installed with a seat height of 17" - 19" from the finished floor, * Complies with following standards: ASME A112.19.2/CSA B45.1 and ASME A112.19.14, In-wall tank & carrier and actuator plate required for installation, If using in-wall tank & carrier other than DuraSystem, # 100691 is mandatory for SensoWash® installation			
Sanitary ceramics with the special WonderGliss surface finish will remain clean and attractive-looking for a long time to come. When ordering WonderGliss please add a "1" as eleventh digit to the model number.			
Actuator plate A1, for toilet, plastic mechanical actuation, for surface mounted installation, dual flush, mounting frame, mounting hardware included, push rods, front plate plastic	8 1/2" x 5 3/4" Inch	0.7 lb	WD5008
Toilet in-wall tank & carrier, Standard for toilets with a projection of <= 24 5/8", adjustable feet 0" - 9 1/2", SensoWash ready, mechanical front flush actuation, includes in-wall tank, marking of filling height, dual flush, insulated against condensation, Scope of delivery, HDPE wall-mounted toilet connection bend DN 90/90, PE wall-mounted toilet connection set DN 90, wall-mounted mounting rods M12, mounting hardware included, 2 bolt caps, cUPC® listed*	23 1/4" x 45 1/4" Inch	35.3 lb	WD1022
Connecting set in combination with SensoWash shower-toilet seat			100691

Vero Air Toilet wall-mounted Duravit Rimless for SensoWash® 
 # 252559..92 / 252559..92

|< 14 5/8" Inch >|

Pre-installation set in combination with SensoWash, for in-wall carrier with horizontal support without shower toilet pre-installation/conduit pipe		005072
Noise reduction gasket for wall-mounted toilet	0.7 lb	005064
Suitable products		
SensoWash® Slim shower-toilet seat for Vero Air* Rear-, Lady- and Comfortwash, individual adjustment of water temperature, spray wand position and water spray intensity, with slow close, night light, remote control included, locking function via remote control, self-cleaning wand, on / off-button, with concealed connections, seat and lid easily removable with one hand, automatic drainage in periods of prolonged disuse, 14 3/4" x 21 1/4" Inch	14 3/4" x 21 1/4" Inch	611500

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.