

C.1 Thermostatic shower trim for concealed installation & # C14200015U10



Thermostatic shower trim for concealed installation	Dimension	Weight	Order number
<p>connection type: rough-in for concealed installation, thermostatic cartridge, square escutcheon 5 7/8" x 5 7/8", 5.4 gal/min (20.6 l/min) flow rate 43.5 psi (3.0 bar), anti-scald 100.4 °F safety stop, rough-in not included, recommended operating pressure 43.5 - 72.5 psi, volume control for 1 outlet, with shut-off valve</p>			
Colors			
10 Chrome			
Variant			
Chrome finish, cUPC® listed*			C14200015U10
Required accessories			
Bluebox® 3/4" BLUEBOX® is a registered trademark of Oras Oy, rough-in for concealed installation, installation depth 3" - 4 1/8", with shut-off valves			GK0900001
Optional accessories			
Shower rail height-adjustable hand shower holder, Ø 3/4"			UV0600002
Shower rail height-adjustable hand shower holder, Ø 3/4"			UV0600001
Shower hose twist-free, with conical hose connector, connection thread 1/2"			UV0610005
Shower hose twist-free, with conical hose connector, connection thread 1/2"			UV0610004
Shower hose twist-free, with conical hose connector, connection thread 1/2"			UV0610003

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.

C.1 Thermostatic shower trim for concealed installation  #
C14200015U10

