



Mirror cabinet	Dimension	Weight	Order number
cEGS/IAPMO®*, LED lighting (4-sided), 1 mirror door, 2 glass shelves (clear glass), back panel inside mirror glass, GFCI outlets are not supplied by the manufacturer (GFCI outlets can be added to the cabinet by a certified electrician on the job site), 1 sensor switch bottom right, mirror cabinets require a GFCI 110 V 60 Hz power source, flat plug will be supplied with the mirror cabinet, LED dimming function, LED (life span > 30,000 hours), LED module permanently enclosed, LED module 3500 Kelvin light color, 36 Watt			
Colors			
M00			
Variant			
	25 5/8" x 6 1/8" I	nch	LC7550L0000
Infobox			
# LC 7550 L/R is available from stock, Stocked item does not include additional modules, Distance between sensor and reflecting surfaces = minimum 3", * Complies with following standards: UL 962 and CSA C22.2 No. 12-1982, Required specification for ordering: - Hinges left (L) or right (R)			
Additional modules cEGS/IAPMO®*, LED downlight for washbasin area 3500 kelvin light color, 3 Watt, LED dimming function, LED (life span > 30,000 hours), LED module permanently enclosed			UV9954
Suitable products			
Magnetic strip in stainless steel , 3 1/2" Inch	3 1/2" Inch		UV9709

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.